

DISTRIBUCIÓN AMARRES METALICOS

Para uso en:

Conductor Desnudo ACSR, AAC

Aislador ANSI Cuello F



De paso (DT)

Catálogo	Rango (mm)		Conductor ACSR, AAC	Piezas	Kilos	Longitud Instalado mm	Color
	Min	Max		Por Caja			
UTF-1205	9.09	10.29	1/0	100	9.45	812.8	Amarillo
UTF-1206	10.31	11.66	2/0	50	8.10	660.4	Azul
UTF-1207	11.68	13.21	3/0	50	8.10	685.8	Naranja
UTF-1209	14.96	16.89	266.8	50	8.55	812.8	Púrpura
UTF-1210	16.92	19.18	336.4	50	9.00	812.8	Café



Lateral (EZ-WRAP)

Catálogo	Rango (mm)		Conductor ACSR, AAC	Piezas	Kilos	Longitud Instalado mm	Color
	Min	Max		Por Caja			
EZSTF-175	9.09	10.29	1/0	100	9.45	584.2	Amarillo
EZSTF-176	10.31	11.66	2/0	100	9.90	635.0	Azul
EZSTF-177	11.68	13.21	3/0	100	10.80	685.8	Naranja
EZSTF-179	14.96	16.89	266.8	100	15.30	787.4	Púrpura
EZSTF-180	16.92	19.18	336.4	100	15.30	863.6	Café

Consulte a PLP para más productos / tipo de conductor

Más información en: www.preformed.com