

DISTRIBUCIÓN

REMATE PLASTIFICADO

Para uso en:
 CONDUCTOR PROTEGIDO (SEMIAISLADO)
 ACSR, AAC



Catálogo	Rango (mm)		Conductor Semiaislado		Piezas	Kilos	Longitud (mm)	Color
	Min	Max	15 kV	25 kV	Por Caja			
ND-0113	14.53	15.44	AAC 1/0	*	50	16.20	838.2	Amarillo
ND-0114	15.47	16.46	ACSR 1/0	*	25	10.80	838.2	Rojo
ND-0116	17.55	18.67	AAC 3/0	AAC 1/0	25	13.50	889	Negro
ND-0117	18.69	19.89	*	ACSR 1/0	25	14.40	914.4	Naranja
ND-0118	19.91	21.18	ACSR 3/0	AAC 3/0	25	15.30	965.2	Azul
ND-0119	21.21	22.56	AAC 266	ACSR 3/0	25	18.00	1,016.0	Negro
ND-0120	22.58	24.00	ACSR 266	*	25	19.80	1,066.8	Amarillo
ND-0121	24.03	25.53	AAC 336	AAC 266	25	23.40	1,117.6	Verde
ND-0122	25.55	27.18	ACSR 336; AAC 477	ACSR 266; AAC 336	10	10.80	1,143.0	Rojo
ND-0123	27.20	28.91	ACSR 477	ACSR 336	10	10.80	1,193.8	Azul

No requiere quitar la cubierta plástica del conductor para lograr el rematado
 Pregunte a PLP por más información técnica y por modelos para 35 kV nominales.